

# 1-PACK EPOXY PRIMER

## Protective Coating



# Indicus

INDICUS 1-PACK EPOXY PRIMER is a protective coating that offers excellent corrosion protection for ferrous surfaces in moderate to highly corrosive environments.



Solvent based



Superior rust protection



For metal surfaces



Excellent adhesion



For interior & exterior use



Enhances life of steel structures

### Areas of Application

INDICUS 1-PACK EPOXY PRIMER can be used:

- on ferrous and surface treated non-ferrous metal works
- in interior and exterior areas

### Technical Properties

Vehicle Type	Epoxy
Specific Gravity	1.30 ± 0.05
Flash Point (IS101/1987 Part 1, Sec 6)	> 30°C
Recommended Thickness	50-75 microns
Stability of Thinned Primer	24 hours
Fire Hazard Class	Flammable

### Working Properties

Finish	Matt
Shade	Grey
Method of Application	Brush or spray
Application Environment	Temperature : 10° to 40° C Humidity : Below 70%
Drying Time at 25°C*	Surface dry : < 1 hour Tack free : < 3 hours
Drying Time To Recoat*	6-8 hours
Dilution With	Epoxy/PU thinner
Ratio of Dilution	15-20% by volume, if required

\* Drying time will vary depending upon the surface & climatic condition, degree of dilution and method of application.



### Coverage

Approximately 90 sq.ft./L per coat at 50 µm DFT.

Coverage is dependent on the degree of dilution, surface condition and method of application.

### Application Procedure

1. Ensure the surface is free from dirt, dust, moisture, adhesion inhibiting compounds like grease, wax, etc. and any loose particles.
2. Blast the surface or sand with emery paper and wipe clean.
3. Apply one coat of primer and allow it to dry for 6 to 8 hours before second coat.
4. If needed, use solvent-based putty to fill cracks and dents to make the surface uniform.
5. After sanding the puttied surface, apply another coat of primer and allow it to dry overnight.
6. Before application of topcoat, lightly sand the surface with emery paper and wipe clean.

### Precautions

- This product is flammable. Avoid extreme temperature.
- Use only in well ventilated areas. Vapours may cause drowsiness and dizziness.
- In case of contact with eyes or skin, wash with water and seek medical advice.
- Keep out of reach of children and away from any combustible materials, food, drinks, etc.

Disclaimer: The product information and applications details given in this data sheet is meant to serve as a general guideline only. Users are advised to undertake a trial for product suitability prior to full-scale usage. There is no express or implied warranty/warranty for the results. The company does not assume any liability or consequential damage for unsatisfactory results, arising from the use of our products.