

CEILING BRIGHT

Bright Emulsion For Ceilings



Indicus

INDICUS CEILING BRIGHT is a water-based acrylic emulsion formulated specifically for ceilings. Its super bright white colour creates a spacious feel and maximises ambient light in the room.



Super bright white



Creates spacious feel



Non-drip



Excellent opacity



Technical Properties

Finish	Matt
Colour	Bright white
Vehicle Type	Acrylic
Specific Gravity	1.40 ± 0.02
Viscosity @ 27 °C	100 KU ± 2
VOC Level	<20 g/L
Drying Time*	Surface dry : 30 to 40 mins. Recoat : 4 to 6 hours
Dilution	Up to 50% with clean water

Coverage

Approximately 220 sq.ft. per litre per coat

* Drying time and coverage will vary depending upon the surface & climatic condition, degree of dilution and method of application.

Precautions

- Diluted paint must be used within 24 hours of dilution.
- Do not over-thin or over-extend the brush.
- In coastal areas, it is recommended to apply the topcoat immediately after the undercoat is dry.
- Close container after each use and store in a cool and dry place.

Application Procedure

Surface Preparation

1. New cementitious surfaces must be properly cured and sound in condition.
2. Ensure the surface is clean, dry and free from seepage, leakage, old paint, dirt, dust and any loose particles.
3. Any growth of fungus, algae or moss needs to be removed thoroughly with wire brush and water.
4. In case of dampness/waterproofing issues, repair the surface using GODRY Waterproofing Solutions.
5. Open non-structural cracks in V-groove and fill with INDICUS EASYSEAL.

Application

1. Prime the surface using INDICUS ULTRAPRIME as per the recommended application procedure.
2. Apply INDICUS ULTRACOAT Wall Putty as per the recommended method to smoothen and level the surface.
3. Apply another coat of INDICUS ULTRAPRIME and allow it to dry.
4. Apply 2-3 coats of CEILING BRIGHT after diluting it with clean water by up to 50%. A gap of 4 to 6 hours should be given between the coats.

Disclaimer: The product information and applications details given in this data sheet is meant to serve as a general guideline only. Users are advised to undertake a trial for product suitability prior to full-scale usage. There is no express or implied warranty/warranty for the results. The company does not assume any liability or consequential damage for unsatisfactory results, arising from the use of our products.