

ULTRACOAT PLUS

Acrylic Wall Putty



Indicus

INDICUS ULTRACOAT PLUS is a water based acrylic wall putty for use in interior areas. It's creamy consistency makes it easier to apply and gives a rich and smooth finish.



Rich & smooth finish



Superior bonding



Improves aesthetics



Improves paint performance



Areas of Application

INDICUS ULTRACOAT PLUS can be used on plastered walls, AAC walls, asbestos, concrete, ceilings, etc. in internal areas.

Technical Properties

Appearance	Viscous paste
Finish	Matt
Colour	White
Specific Gravity	1.76 ± 0.02
Drying Time*	Touch dry : 30 mins. Recoat : 4 to 6 hours
Full Curing*	6 to 8 hours
Dilution	Not needed. If required, clean water can be added.

Coverage

Approximately 25 sq.ft. per kg per coat

* Drying time, full curing and coverage will vary depending upon the surface & climatic condition, degree of dilution and method of application.

Application Procedure

Surface Preparation

1. New cementitious surfaces must be properly cured, clean and sound in condition.
2. In case of dampness/waterproofing problems, repair the surface using GODRY Waterproofing Solutions.
3. Open non-structural cracks, if any, in V-groove and fill with INDICUS EASYSEAL.

Application

1. Moisten the wall with sufficient quantity of clean water.
2. Apply one coat of INDICUS ULTRAPRIME wall primer and apply ULTRACOAT PLUS with the help of a putty knife.
3. Allow the first coat to dry for 4 to 6 hours and apply a second coat if needed.
4. Allow the putty to cure for 6 to 8 hours, preferably overnight.
5. Use fine emery paper to remove application marks, if any.
6. Apply another coat of INDICUS ULTRAPRIME wall primer and finish with topcoat.

Disclaimer: The product information and applications details given in this data sheet is meant to serve as a general guideline only. Users are advised to undertake a trial for product suitability prior to full-scale usage. There is no express or implied warranty/warranty for the results. The company does not assume any liability or consequential damage for unsatisfactory results, arising from the use of our products.