

WOOD PRIMER

Wood Coating



Indicus

INDICUS WOOD PRIMER is a solvent-based protective coating for wooden surfaces. It fills wood grains, blocks absorption of moisture and provides a sound base for topcoats.



Solvent based



For wooden surfaces



For interior & exterior use

Areas of Application

INDICUS WOOD PRIMER can be used:

- on wooden surfaces
- in both interior and exterior areas

Features

- Superior wood penetration
- Excellent intercoat adhesion
- Good flow & levelling
- Enhances life of topcoat

Technical Properties

| | |
|---|---------------|
| Vehicle Type | Alkyd |
| Specific Gravity | 1.25 ± 0.1 |
| Flash Point (IS101/1987 Part 1, Sec 6) | > 30°C |
| Recommended Thickness | 40-60 microns |
| Stability of Thinned Primer | 24 hours |
| Fire Hazard Class | Flammable |

Precautions

- This product is flammable. Avoid extreme temperature.
- Use only in well ventilated areas. Vapours may cause drowsiness and dizziness.
- In case of contact with eyes or skin, wash with water and seek medical advice.
- Keep out of reach of children and away from any combustible materials, food, drinks, etc.



Working Properties

| | |
|------------------------|---|
| Finish | Matt |
| Shade | White |
| Method of Application | Brush, roller or spray |
| Drying Time at 25°C* | Surface dry : < 1 hour Tack free : < 3 hours |
| Drying Time To Recoat* | 6-8 hours |
| Dilution with | Mineral Turpentine Oil (MTO) |
| Ratio of Dilution | Up to 10%, if required |
| Coverage* | 130 sq.ft./L/coat at 40 DFT. |

* Drying time and coverage will vary depending upon the surface & climatic condition, degree of dilution and method of application.

Application Procedure

1. Ensure the surface is free from dirt, dust, moisture, adhesion inhibiting compounds like grease, wax, etc. and any loose particles.
2. Sand with emery paper and wipe clean.
3. Apply one coat of primer and allow it to dry for 6 to 8 hours.
4. If needed, use solvent-based putty to fill cracks and dents to make the surface uniform.
5. After sanding the puttied surface, apply another coat of primer and allow it to dry overnight.
6. Before application of topcoat, lightly sand the surface with emery paper and wipe clean.

Disclaimer: The product information and applications details given in this data sheet is meant to serve as a general guideline only. Users are advised to undertake a trial for product suitability prior to full-scale usage. There is no express or implied warranty/warranty for the results. The company does not assume any liability or consequential damage for unsatisfactory results, arising from the use of our products.