

GODRY AQUASEAL

Waterproof Coating



Indicus

INDICUS GODRY AQUASEAL is an acrylic waterproof coating for all types of cementitious surfaces in exterior areas. It forms a durable and elastic membrane that provides excellent waterproofing for a building. The specially added polyester fibres deliver excellent mechanical properties and adhesion.



Reinforced with fibres
for superior mechanical properties



Flexible



5 years waterproofing warranty*



Durable



Crack bridging



Anti-algal



Efflorescence resistant



Technical Properties

Colour	White
Specific Gravity	1.36 ± 0.05
Viscosity @ 27 °C	120 KU ± 5
Tensile Strength	>2.5 N/mm ²
Application Temperature	5°C to 35°C
VOC Level	<20 g/L
Drying Time ¹	Surface Dry : 30 to 40 mins. Recoat : 4 to 6 hours

¹ Drying time and coverage will vary depending upon the surface & climatic condition, degree of dilution and method of application.

Coverage

- On horizontal surface, approx. 10 sq.ft./L for 3 coats.
- On vertical surface, approx. 25 sq.ft./L for 2 coats.

Coverage is dependent on the degree of dilution, surface condition and method of application.

Shelf Life & Storage

Shelf life is 36 months from the date of manufacturing, if stored in unopened and original packaging. Store in dry place away from direct sunlight.

Application Procedure

1. Clean the surface thoroughly and repair the damages, if any, using polymer modified repair mortar.
2. New cementitious surfaces should be allowed to cure for minimum of 28 days before coating.

On Horizontal Surface

1. Apply one self-priming coat by diluting AQUASEAL with 30% clean water on the surface and allow it to dry.
2. Apply one undiluted coat of AQUASEAL and allow it to dry.
3. Apply the second undiluted coat of AQUASEAL perpendicular to the first coat.

On Vertical Surface

1. Apply one self-priming coat by diluting AQUASEAL with 10% water on the surface and allow it to dry.
2. Apply one undiluted coat of AQUASEAL and once dried, complete with top coat.

* Conditions apply. Please refer INDICUS GODRY AQUASEAL Warranty Guide for conditions and information on the warranty available at www.indicus.in/warranty.

Disclaimer: The product information and applications details given in this data sheet is meant to serve as a general guideline only. Users are advised to undertake a trial for product suitability prior to full-scale usage. There is no express or implied warranty/warranty for the results. The company does not assume any liability or consequential damage for unsatisfactory results, arising from the use of our products.