

ULTRAPRIME

High Performance Wall Primer



Indicus

INDICUS ULTRAPRIME is a high-performance water-based acrylic primer. It delivers unmatched penetration, adhesion and opacity, making it the perfect choice of primer.



Superior adhesion
for a long lasting top coat



Higher coverage*



Thicker for a uniform finish



For exterior & interior use

Areas of Application

INDICUS ULTRAPRIME:

- is suitable for priming masonry surfaces, concrete, asbestos sheets, hard & soft board, etc.
- can be used in both interior and exterior areas

Features

- Outstanding adhesion
- Higher coverage
- Smooth & uniform base
- Reduces porosity
- Excellent opacity

Technical Properties

Colour	White
Vehicle Type	Acrylic
Specific Gravity	1.40 ± 0.01
Viscosity @ 27 °C	100 KU ± 1
VOC Level	<20 g/L
Drying Time*	Surface dry : 30 to 40 mins. Recoat : 4 to 6 hours
Dilution	Up to 50% with clean water

Coverage

Approximately 130 sq.ft. per litre per coat



* Drying time and coverage will vary depending upon the surface & climatic condition, degree of dilution and method of application.



Application Procedure

Surface Preparation

1. New masonry surfaces must be properly cured and sound in condition.
2. Ensure the surface is clean, dry and free from seepage, leakage, old paint, dirt, dust and any loose particles.
3. Any growth of fungus, algae or moss needs to be removed thoroughly with wire brush and water.
4. In case of dampness/waterproofing issues, repair the surface using GODRY Waterproofing Solutions.
5. Open non-structural cracks in V-groove and fill with INDICUS EASYSEAL.

Application

1. Apply one coat of ULTRAPRIME after diluting it with clean water and allow the coat to dry for 4 to 6 hours.
2. Apply INDICUS ULTRACOAT Wall Putty as per the recommended application method.
3. Apply the second coat of ULTRAPRIME and allow it to dry.
4. Apply one extra coat if needed or apply top coat within 7 days of primer application.

Precautions

- Do not over-thin or over-extend the brush.
- In coastal areas, it is recommended to apply the topcoat immediately after the undercoat is dry.
- Close container after each use and store in a cool and dry place.

Disclaimer: The product information and applications details given in this data sheet is meant to serve as a general guideline only. Users are advised to undertake a trial for product suitability prior to full-scale usage. There is no express or implied warranty/warranty for the results. The company does not assume any liability or consequential damage for unsatisfactory results, arising from the use of our products.