

# WALLPRIME

Multi-purpose Wall Primer



# Indicus

INDICUS WALLPRIME is a water-based acrylic primer suitable for priming masonry surfaces. It provides an optimum base for the application of subsequent coats of putty and topcoat.



Smooth to apply



Good brightness



Reduced Porosity



For exterior & interior use

## Areas of Application

INDICUS WALLPRIME:

- is suitable for priming masonry surfaces, concrete, asbestos sheets, hard & soft board, etc.
- can be used in both interior and exterior areas.

## Features

- Smooth to apply
- Good inter-coat adhesion
- Reduces porosity
- Good opacity
- Multi-purpose

## Technical Properties

Colour	White
Vehicle Type	Acrylic
Specific Gravity	1.38 ± 0.01
Viscosity @ 27 °C	90 KU ± 2
VOC Level	<20 g/L
Drying Time*	Surface dry : 30 to 40 mins. Recoat : 4 to 6 hours
Dilution	Up to 50% with clean water

## Coverage

Approximately 100 sq.ft. per litre per coat



\* Drying time and coverage will vary depending upon the surface & climatic condition, degree of dilution and method of application.



## Application Procedure

### Surface Preparation

1. New cementitious surfaces must be properly cured and sound in condition.
2. Ensure the surface is clean, dry and free from seepage, leakage, old paint, dirt, dust and any loose particles.
3. Any growth of fungus, algae or moss needs to be removed thoroughly with wire brush and water.
4. In case of dampness/waterproofing issues, repair the surface using GODRY Waterproofing Solutions.
5. Open non-structural cracks in V-groove and fill with INDICUS EASYSEAL.

### Application

1. Apply one coat of WALLPRIME after diluting it with clean water and allow the coat to dry for 4 to 6 hours.
2. Apply INDICUS ULTRACOAT Wall Putty as per the recommended application method.
3. Apply the second coat of WALLPRIME and allow it to dry.
4. Apply one extra coat if needed or apply top coat within 7 days of primer application.

### Precautions

- Do not over-thin or over-extend the brush.
- In coastal areas, it is recommended to apply the topcoat immediately after the undercoat is dry.
- Close container after each use and store in a cool and dry place.

Disclaimer: The product information and applications details given in this data sheet is meant to serve as a general guideline only. Users are advised to undertake a trial for product suitability prior to full-scale usage. There is no express or implied warranty/warranty for the results. The company does not assume any liability or consequential damage for unsatisfactory results, arising from the use of our products.