

ADMYRA

Spray Paint



Indicus

INDICUS ADMYRA Spray Paint is an ultra-acrylic aerosol suitable for use on most surfaces in interior and exterior areas. It enhances the appeal of the painted surface and comes in variety of colours.



Smooth & Glossy Finish

Makes the painted surface more attractive.



Weather Resistant

Provides tough barrier against variable atmospheric conditions.



UV Resistant

Gives good protection from UV degradation, except for chrome effect and fluorescent colours.



Quick Drying

Dries faster, making way for faster operations.

Areas of Application

INDICUS ADMYRA Spray Paint can be used:

- on canvas, paper, metal, wood and wall surfaces
- in decorative and creative painting, and graffiti works
- in internal and exteriors areas

Technical Properties

Property	Result
Solids (%)	27 ± 5
Density at 30° C	1.03 ± 0.02
Flash Point	<0° C
Touch Dry*	3-5 mins.
Tack Free Dry*	30 mins.
Hard Dry*	24 hrs.
Coverage*	12-15 sq. ft. per 400 ml can

* Will vary depending upon the climatic & surface conditions.

Environmental Security

- Avoid release to the environment.
- Do not empty into drains or water course.
- Empty packaging and paint residues are to be disposed of as chemical waste.
- Dispose of contents and containers in accordance with all local, regional, national and international regulations.
- Only the completely emptied cans should be put into the recycling skip or appropriate container.



Application Procedure

1. Ensure surface is thoroughly clean, dry and free from any loose particles and contaminations.
2. For repainting application, sand away the old paint or varnish layers.
3. Any cracks should be filled with suitable filling compounds.
4. Shake the aerosol can well for 1-2 minutes till you hear the clear sound of agitator ball before use. Shake occasionally during use to avoid clogging.
5. Hold the aerosol can vertically and apply in thin even layers at a distance of around 25 cm from the surface.
6. Apply 2-3 coats in a stroking motion with a gap of at least 10-15 mins between the coats. Apply successive coats crosswise to each other.
7. After use, turn the can upside down and spray until gas escapes to prevent clogging.
8. If the spray nozzle is clogged, rinse it with thinner.

Precautions

- Work in well ventilated areas.
- Use suitable personal protection equipment.
- Do not breathe vapour/spray.
- Do not get in eyes, on skin or on clothing.
- Keep away from food drinks and animal feed.
- Don't spray on open flame or other ignition source.

Warning

- Extremely flammable aerosol. Pressurised container may burst if heated.
- Do not pierce or burn even after using.
- Do not breathe or inhale vapour/spray.
- Don't spray on open flame or other ignition source.
- Do not expose to temperature above 45°C.
- Avoid release to the environment.

Disclaimer: The product information and applications details given in this data sheet is meant to serve as a general guideline only. Users are advised to undertake a trial for product suitability prior to full-scale usage. There is no express or implied guaranty/warranty for the results. The company does not assume any liability or consequential damage for unsatisfactory results, arising from the use of our products.