

# GODRY EASYSEAL

Water Resistant Crack Filler



# Indicus

INDICUS GODRY EASYSEAL is a ready-to-use high performance crack filling compound for both interior and exterior surfaces. It is flexible, water-resistant, adheres to variety of porous surfaces and can be sanded to a smooth finish.

## Features

- **Water-resistant**  
Stops ingress of water through cracks
- **Superior flexibility**  
Accommodates minor movements
- **Durable**  
Resistance to UV & atmospheric conditions
- **Excellent adhesion**  
Bonds strongly to all cementitious substrates
- **High tack**  
Quickly bonds with variety of substrates

## Areas of Application

Indicus Godry Easyseal can be used:

- To fills cracks up to 5 mm width
- On various porous surfaces
- In interior & exterior areas

## Technical Properties

Appearance	Viscous paste
Colour	White
Specific Gravity	1.56 ± 0.02
Drying Time*	4 to 6 hours
Full Curing Time	7 days

\* Drying time will vary depending upon the surface condition, degree of dilution and method of application.

## Coverage

Approximately 30 running meter per kg for a depth of 5 mm and width of 5 mm.



## Application Procedure

1. Ensure the crack is clean, dry and free any loose particles.
2. Fine hairline cracks must be widened up to minimum 1 mm by forming a V-groove.
3. Apply a coat of INDICUS ULTRAPRIME wall primer over the crack.
4. Press EASYSEAL into the crack while the surface is tacky using a putty knife or spatula.
5. Allow it to dry for 12 hours and apply second coat.
6. Application of subsequent coat can begin once second coat has completely dried.
7. For best results, allow EASYSEAL paste to air cure for 7 days.

## Precautions

- Strictly not recommended for cracks more than 5 mm width.
- Do not use for filling structural cracks, expansion joints, separation gaps, etc.

Disclaimer: The product information and applications details given in this data sheet is meant to serve as a general guideline only. Users are advised to undertake a trial for product suitability prior to full-scale usage. There is no express or implied guaranty/warranty for the results. The company does not assume any liability or consequential damage for unsatisfactory results, arising from the use of our products.