

# GLAZ

## Aluminium Paint



# Indicus

INDICUS GLAZ Aluminium Paint is a two-pack general purpose aluminium paint that gives a very good lustre. It is highly durable, provides excellent corrosion & heat resistance and reflects light. It can be used on suitably prepared metal and wooden surfaces.



Lustre finish



Excellent durability



Corrosion resistant



Reflects heat



Solvent based



For interior & exterior use

### Areas of Application

INDICUS GLAZ Aluminium Paint can be used:

- on suitably prepared metal and wooden surfaces
- in both interior and exterior areas

### Technical Properties

Flash Point	>30°C
Recommended Thickness / Coat	15 to 20 microns
Fire Hazard Class	Flammable

### Working Properties

Finish	High lustre
Shade	Aluminium
Method of Application	Brush or spray
Drying Time* at 25°C	Surface dry : 4 to 6 hours Hard dry : 8 to 10 hours
Washability	High
Dilution	Not recommended
Pot Life	48 hours
Coverage*	Approx. 140 sq.ft./L for two coats

\* Drying time and coverage will vary depending upon the surface & climatic condition, degree of dilution and method of application.



### Application Procedure

1. Ensure the surface is free from dirt, dust, moisture, adhesion inhibiting compounds like grease, wax, etc. and any loose particles.
2. Apply a coat of appropriate primer and allow it to dry.
3. Use oil-based putty to fill cracks and dents, if any, to make the surface uniform.
4. Apply another coat of primer and allow it to dry.
5. Mix the entire quantity of aluminium paste with a small quantity of medium.
6. Then add the balance medium to the mixture and stir vigorously.
7. Apply two coats with an interval of 8 hours between successive coats.

### Precautions

- This product is flammable. Avoid extreme temperature.
- Use only in well ventilated areas. Vapours may cause drowsiness and dizziness.
- In case of contact with eyes or skin, wash with water and seek medical advice.
- Keep out of reach of children and away from any combustible materials, food, drinks, etc.

Disclaimer: The product information and applications details given in this data sheet is meant to serve as a general guideline only. Users are advised to undertake a trial for product suitability prior to full-scale usage. There is no express or implied warranty/warranty for the results. The company does not assume any liability or consequential damage for unsatisfactory results, arising from the use of our products.