

# ULTRACOAT PLUS

Acrylic Wall Putty



# Indicus

INDICUS ULTRACOAT PLUS is a water based acrylic wall putty for use in interior areas. It's creamy consistency makes it easier to apply and gives a rich and smooth finish.



Rich & smooth finish



Superior bonding



Improves aesthetics



Improves paint performance



## Areas of Application

INDICUS ULTRACOAT PLUS can be used on plastered walls, AAC walls, asbestos, concrete, ceilings, etc. in internal areas.

## Technical Properties

Appearance	Viscous paste
Finish	Matt
Colour	White
Specific Gravity	1.76 ± 0.02
Drying Time*	Touch dry : 30 mins. Recoat : 4 to 6 hours
Full Curing*	6 to 8 hours
Dilution	Not needed. If required, clean water can be added.

## Coverage

Approximately 25 sq.ft. per kg per coat

\* Drying time, full curing and coverage will vary depending upon the surface & climatic condition, degree of dilution and method of application.

## Application Procedure

### Surface Preparation

1. New cementitious surfaces must be properly cured, clean and sound in condition.
2. In case of dampness/waterproofing problems, repair the surface using GODRY Waterproofing Solutions.
3. Open non-structural cracks, if any, in V-groove and fill with INDICUS EASYSEAL.

### Application

1. Moisten the wall with sufficient quantity of clean water.
2. Apply one coat of INDICUS ULTRAPRIME wall primer and apply ULTRACOAT PLUS with the help of a putty knife.
3. Allow the first coat to dry for 4 to 6 hours and apply a second coat if needed.
4. Allow the putty to cure for 6 to 8 hours, preferably overnight.
5. Use fine emery paper to remove application marks, if any.
6. Apply another coat of INDICUS ULTRAPRIME wall primer and finish with topcoat.

Disclaimer: The product information and applications details given in this data sheet is meant to serve as a general guideline only. Users are advised to undertake a trial for product suitability prior to full-scale usage. There is no express or implied warranty/warranty for the results. The company does not assume any liability or consequential damage for unsatisfactory results, arising from the use of our products.