

ULTRACOAT

Wall Putty



Indicus

INDICUS ULTRACOAT is a white cement based water-resistant wall putty that provides a smooth and durable base for the application of paints. It's unique properties deliver superior bonding with the substrate and extended life of paints.

Features

- White & smooth finish
- Excellent workability
- Superior bonding
- 10% higher coverage
- Water-resistant
- Good breathability

Areas of Application

INDICUS ULTRACOAT is:

- ideal for finishing and decorating all kinds of exterior and interior walls
- can be applied on new and old walls (after removing the existing base coat)

Technical Properties

Property	Result
Initial Setting Time (min.)	≥200
Final Setting Time (min.)	≤500
Mixing Ratio	35-40% by weight
Coverage	Approximately 18 to 22 sq. ft. per kg in double coat

Note: Results will vary depending upon the surface & climatic condition, degree of dilution and method of application.

Precautions

- Always add powder to water & never water to powder.
- Do not attempt to increase pot life by adding water.
- Use only clean water for mixing.



Application Procedure

Surface Preparation

1. New cementitious surfaces must be properly cured, clean and sound in condition.
2. Ensure the surface is clean, dry and free from seepage, leakage, old paint, dirt, dust and any loose particles.
3. In case of dampness/waterproofing problems, repair the surface using INDICUS GODRY Waterproofing Solutions.

Application

1. Moisten the wall with sufficient quantity of clean water.
2. Mix INDICUS ULTRACOAT with 35 to 40% clean water by weight and continue mixing until a homogeneous lump-free paste of desired consistence is obtained.
3. Mix only the quantity which can be applied within the workable time.
4. Apply the first coat uniformly on the moistened surface with the help of putty blade or trowel.
5. When first coat is dry, apply the second coat with fresh material and allow it to dry.
6. Use fine emery paper to remove application marks, if any.

Disclaimer: The product information and applications details given in this data sheet is meant to serve as a general guideline only. Users are advised to undertake a trial for product suitability prior to full-scale usage. There is no express or implied guaranty/warranty for the results. The company does not assume any liability or consequential damage for unsatisfactory results, arising from the use of our products.